

PR

Portable Single Phase Relay Type

500VA-2000VA



Features:

- ◆ CPU control
- ◆ Component damage protection
- ◆ Short circuit and overload protection
- ◆ Selectable delay time
- ◆ Over temperature protection
- ◆ LED indicators to show status of working, over voltage, and low voltage
- ◆ Automatic voltage regulation/Extension socket
- ◆ Protection against brownouts and over voltages
- ◆ Digital meter indicates line voltage and output voltage
- ◆ Surge, spike, and lightning protection (optional)



• Technical Parameter

Specification		500VA	1000VA	1500VA	2000VA
Input	Phase	Single phase			
	Voltage	AC 125V-270V / 140V-260V			
	Frequency	50Hz/60Hz			
Output	Voltage	AC 220V ±10%			
	Capacity	250W	500W	750W	1000W
	Frequency	50Hz/60Hz			
Protection	Low voltage	184V±5V			
	Over voltage	246V±5V			
	Time Delay	5s / 255s			
	Overload/ short circuit	Fuse/MCB			
Packaging	Pcs per Carton	9			
	Net Wt.(kg)	1.3	1.6	1.75	1.8
	Shipping Wt.(kg)	11.9	14.3	15.5	16.8
	Package dimensions (mm)	528*320*360			
Efficiency	AC-AC	95%			
Acoustic	Noise level	≤50dB			
Environment	Temperature	-5°C to 40°C			
	Humidity	20% to 90%			

• Product Appearance



Euro Standard



Multifunctional Socket



H:7.5CM



W:14.0CM

L:26.0CM



H:9.9CM



W:13.5CM

E:26.0CM